


Specifications


| Model Name | | MS5512/AR (Special AR Coating) MS5512/F (Protective Filter) | MS3512/AR (Special AR Coating) MS3512/F (Protective Filter) | MS2512/AR (Special AR Coating) MS2512/F (Protective Filter) |
|--------------------------|-------------------------------|--|--|--|
| LCD Panel | Technology | 21.3-inch, TFT monochrome active matrix IPS technology | 21.3-inch, TFT monochrome active matrix IPS technology | 21.3-inch, TFT monochrome active matrix IPS technology |
| | Display Area | 422.40mm X 337.92mm | 433.152mm X 324.864mm | 432mm X 324mm |
| | Pixel Pitch | 0.165mm X 0.165mm | 0.2115mm X 0.2115mm | 0.270mm X 0.270mm |
| | Contrast Ratio | 1200 : 1 (typ) | 1400 : 1 (typ) | 1400 : 1 (typ) |
| | Maximum Luminance | 1200cd/m ² typ. (calibrated to 500cd/m ² and 410cd/m ² by factory default) | 1700cd/m ² typ. (calibrated to 500cd/m ² and 410cd/m ² by factory default) | 1900cd/m ² typ. (calibrated to 410cd/m ² by factory default) |
| Visual Performance | Viewing Angle | 176° vertical and horizontal (Wide view) | 170° vertical and horizontal | 170° vertical and horizontal |
| | Native Resolution | 2048 X 2560, Independent Sub pixel Drive technology ON: 2048 X 7680 (sub-pixel) | 1536 X 2048, Independent Sub pixel Drive technology ON: 1536 X 6144 (sub-pixel) | 1200 X 1600, Independent Sub pixel Drive technology ON: 1200 X 4800 (sub-pixel) |
| Interface | Input Signal | DVI-D (DVI 1.0 compliant) DisplayPort (DisplayPort 1.1a compliant) | DVI-D (DVI 1.0 compliant) DisplayPort (DisplayPort 1.1a compliant) | DVI-D (DVI 1.0 compliant) DisplayPort (DisplayPort 1.1a compliant) |
| | Plug and Play | DDC2B compliant | DDC2B compliant | DDC2B compliant |
| Input Power Supply | Input | 100V ~ 240V (±10%) 50/60Hz | 100V ~ 240V (±10%) 50/60Hz | 100V ~ 240V (±10%) 50/60Hz |
| | Maximum Power Consumption | 80W | 60W | 60W |
| Features | Calibration Control | Luminance, Gamma, Capability of saving 3 sets of LUT settings (An optional calibration kit is required) | Luminance, Gamma, Capability of saving 3 sets of LUT settings (An optional calibration kit is required) | Luminance, Gamma, Capability of saving 3 sets of LUT settings (An optional calibration kit is required) |
| | OSD Information Display | Model name, Serial No., Total operating time, Calibration settings (Operating time from last calibration, Luminance, Gamma), Current luminance | Model name, Serial No., Total operating time, Calibration settings (Operating time from last calibration, Luminance, Gamma), Current luminance | Model name, Serial No., Total operating time, Calibration settings (Operating time from last calibration, Luminance, Gamma), Current luminance |
| | USB Hub | USB Rev. 2.0 compliant, Self-powered USB upstream connector (x1), USB downstream connector (x2) | USB Rev. 2.0 compliant, Self-powered USB upstream connector (x1), USB downstream connector (x2) | USB Rev. 2.0 compliant, Self-powered USB upstream connector (x1), USB downstream connector (x2) |
| | Other Features | Luminance uniformity correction, Hardware pivot, LED indicator, Configurations switching function, Independent Sub pixel Drive technology, Self DICOM check function | Luminance uniformity correction, Hardware pivot, LED indicator, Configurations switching function, Independent Sub pixel Drive technology, Self DICOM check function | Luminance uniformity correction, Hardware pivot, LED indicator, Configurations switching function, Independent Sub pixel Drive technology, Self DICOM check function |
| Approvals | | ANSI/AAMI ES60601-1(2005), CAN/CSA C22.2 NO. 60601-1(2008), CE (EN60601-1, EN60601-1-2), FCC Part15, subpart B Class B, VCCI class B, FDA510(k), J-Moss, RoHS, ICES-3(B) | ANSI/AAMI ES60601-1(2005), CAN/CSA C22.2 NO. 60601-1(2008), CE (EN60601-1, EN60601-1-2), FCC Part15, subpart B Class B, VCCI class B, J-Moss, RoHS, ICES-3(B), [FDA510(k) pending] | ANSI/AAMI ES60601-1(2005), CAN/CSA C22.2 NO. 60601-1(2008), CE (EN60601-1, EN60601-1-2), FCC Part15, subpart B Class B, VCCI class B, J-Moss, RoHS, ICES-3(B), [FDA510(k) pending] |
| Physical Characteristics | Dimensions (incl. tilt stand) | Landscape : 474.5 (W) X 482.9 / 544.4 (H) X 220 (D)mm Portrait : 390 (W) X 525.15 / 586.65 (H) X 220 (D)mm | Landscape : 474 (W) X 468.4 / 529.9 (H) X 220 (D)mm Portrait : 367 (W) X 521.9 / 583.4 (H) X 220 (D)mm | Landscape : 474 (W) X 468.4 / 529.9 (H) X 220 (D)mm Portrait : 367 (W) X 521.9 / 583.4 (H) X 220 (D)mm |
| | Weight | About 13kg | About 12kg | About 12kg |
| | Tilt Stand | Tilt, Swivel, Portrait / Landscape | Tilt, Swivel, Portrait / Landscape | Tilt, Swivel, Portrait / Landscape |
| | Mount | 100mm VESA mounting | 100mm VESA mounting | 100mm VESA mounting |
| | Security Slot | On the back of the panel and the tilt stand | On the back of the panel and the tilt stand | On the back of the panel and the tilt stand |
| Accessories | | Power cord, DVI cable, DisplayPort cable, USB cable, Operation manual *Cleaning kit (Special AR coating model only) | Power cord, DVI cable, DisplayPort cable, USB cable, Operation manual *Cleaning kit (Special AR coating model only) | Power cord, DVI cable, DisplayPort cable, USB cable, Operation manual *Cleaning kit (Special AR coating model only) |

| Model Name | | CCL35812/AR (Special AR Coating) CCL35812/F (Protective Filter) | CCL25812/AR (Special AR Coating) CCL25812/F (Protective Filter) |
|--------------------------|-------------------------------|--|--|
| LCD Panel | Technology | 21.3-inch, TFT color active matrix IPS technology | 21.3-inch, TFT color active matrix IPS technology |
| | Display Area | 433.152mm X 324.864mm | 432mm X 324mm |
| | Pixel Pitch | 0.2115mm X 0.2115mm | 0.270mm X 0.270mm |
| | Contrast Ratio | 1400 : 1 (typ) | 1400 : 1 (typ) |
| | Maximum Luminance | 800cd/m ² typ. (calibrated to 410cd/m ² and 300cd/m ² by factory default) | 900cd/m ² typ. (calibrated to 410cd/m ² and 300cd/m ² by factory default) |
| Visual Performance | Viewing Angle | 176° vertical and horizontal | 176° vertical and horizontal |
| | Native Resolution | 1536 X 2048 | 1200 X 1600 |
| Interface | Input Signal | DVI-D (DVI 1.0 compliant), DisplayPort (DisplayPort 1.1a compliant) | DVI-D (DVI 1.0 compliant), DisplayPort (DisplayPort 1.1a compliant) |
| | Plug and Play | DDC2B compliant | DDC2B compliant |
| Input Power Supply | Input | 100V ~ 240V (±10%) 50/60Hz | 100V ~ 240V (±10%) 50/60Hz |
| | Maximum Power Consumption | 80W | 75W |
| Features | Calibration Control | Luminance, Gamma, Capability of saving 3 sets of LUT settings (An optional calibration kit is required) | Luminance, Gamma, Capability of saving 3 sets of LUT settings (An optional calibration kit is required) |
| | OSD Information Display | Model name, Serial No., Total operating time, Calibration settings (Operating time from last calibration, Luminance, Gamma), Current luminance | Model name, Serial No., Total operating time, Calibration settings (Operating time from last calibration, Luminance, Gamma), Current luminance |
| | USB Hub | USB Rev. 2.0 compliant, Self-powered USB upstream connector (x1), USB downstream connector (x2) | USB Rev. 2.0 compliant, Self-powered USB upstream connector (x1), USB downstream connector (x2) |
| | Other Features | Luminance and color uniformity correction, Hardware pivot, LED indicator, Configurations switching function, Self DICOM check function | Luminance and color uniformity correction, Hardware pivot, LED indicator, Configurations switching function, Self DICOM check function |
| Approvals | | ANSI/AAMI ES60601-1(2005), CAN/CSA C22.2 NO. 60601-1(2008), CE (EN60601-1, EN60601-1-2), FCC Part15, subpart B Class B, VCCI class B, J-Moss, RoHS, FDA510(k), ICES-3(B) | ANSI/AAMI ES60601-1(2005), CAN/CSA C22.2 NO. 60601-1(2008), CE (EN60601-1, EN60601-1-2), FCC Part15, subpart B Class B, VCCI class B, J-Moss, RoHS, FDA510(k), ICES-3(B) |
| Physical Characteristics | Dimensions (incl. tilt stand) | Landscape : 474 (W) X 468.4 / 529.9 (H) X 220 (D)mm Portrait : 367 (W) X 521.9 / 583.4 (H) X 220 (D)mm | Landscape : 474 (W) X 468.4 / 529.9 (H) X 220 (D)mm Portrait : 367 (W) X 521.9 / 583.4 (H) X 220 (D)mm |
| | Weight | About 12kg | About 12kg |
| | Tilt Stand | Tilt, Swivel, Portrait / Landscape | Tilt, Swivel, Portrait / Landscape |
| | Mount | 100mm VESA mounting | 100mm VESA mounting |
| | Security Slot | On the back of the panel and the tilt stand | On the back of the panel and the tilt stand |
| Accessories | | Power cord, DVI cable, DisplayPort cable, USB cable, Operation manual *Cleaning kit (Special AR coating model only) | Power cord, DVI cable, DisplayPort cable, USB cable, Operation manual *Cleaning kit (Special AR coating model only) |


MS5512



MS3512 / MS2512 / CCL25812 / CCL35812



●“TOTOKU” is a brand of medical and industrial displays that JVCKENWOOD develops. ●Company names and product names are the trademarks or registered trademarks of the respective companies. ●Product specifications and appearance are subject to change without notice. ●Colors in photographs may differ from actual colors due to the printing process. ●Images on screens are simulated.

**Safety Precautions**

- Please read the user's manual for safe and proper use.
- Do not expose the product to dust, moisture, steam, or oily smoke. It could cause fire, electric shock, or a failure.

Please contact the distributor below with inquiries and orders.

Healthcare Systems Operation, Professional & Healthcare Division
JVCKENWOOD Corporation
3-12, Moriya-cho, Kanagawa-ku, Yokohama-shi, Kanagawa, 221-0022, Japan
TEL : +81-45-450-1908 FAX : +81-45-450-1926
E mail : medical-display.j@jvckenwood.com



Effective October 1, 2011, JVCKENWOOD Corporation merged with three companies, Victor Company of Japan, Ltd., Kenwood Corporation and J&K Car Electronics Corporation. Under the Corporate Vision "Creating excitement and peace of mind for the people of the world", we will focus on our image technologies, acoustic technologies, radio equipment, and audio and visual software, using these as the core of our aims to become a business group whose sound, images, and radio communications products and drivers make communication a reality for the people of the world.

TOTOKU

MS&CCL Series



Flat Display Systems for Medical Imaging



Higher Image Quality and Total Management

— DICOM Conformance —

Monochrome



5 Megapixel + Independent Sub pixel Drive technology

MS55i2

MS55i2/AR (Special AR Coating)
MS55i2/F (Protective Filter)

21.3"

DisplayPort & DVI-D

1200

cd/m²

1200:1

Calibration function

16Bit LUT

10-bit display

LED Backlight


Color/Monochrome Conversion

OSD

Luminance Uniformity Correction

Hardware Pivot

LED Indicator



3 Megapixel + Independent Sub pixel Drive technology

MS35i2

MS35i2/AR (Special AR Coating)
MS35i2/F (Protective Filter)

21.3"

DisplayPort & DVI-D

1700

cd/m²

1400:1

Calibration function

16Bit LUT

10-bit display

LED Backlight

Color/Monochrome Conversion

OSD

Luminance Uniformity Correction

Hardware Pivot

LED Indicator



2 Megapixel + Independent Sub pixel Drive technology

MS25i2

MS25i2/AR (Special AR Coating)
MS25i2/F (Protective Filter)

21.3"

DisplayPort & DVI-D

1900

cd/m²

1400:1

Calibration function

16Bit LUT

10-bit display

LED Backlight

Color/Monochrome Conversion

OSD

Luminance Uniformity Correction

Hardware Pivot

LED Indicator

Reliable Quality and Stability

Higher contrast with the new IPS panel

The new IPS panel provides crisper images and more confidence in diagnostic precision.




Longer lifetime and energy saving with LED backlight

Compared to the current models, the new MS Series with the LED backlight system saves about 20% energy and will hold brightness longer.




Luminance stabilizing system λ-Sentinel

λ-Sentinel consists of a luminance sensor and a luminance control circuit. The luminance sensor is integrated into the front bezel, directly against the screen, and constantly monitors and accurately stabilizes luminance on the screen surface by sending feedback instantaneously to the control circuit.




- With luminance fluctuation caused by the LCD module taken into account, highly accurate luminance control is achieved.
- Actual luminance measurements including intermediate luminance are taken on the screen surface.



Independent Sub pixel Drive technology

Driven by each sub-pixel value corresponding to detailed information recorded in an original image, three times resolution enhancement is achieved. In addition, up to 1276 shades of gray are now simultaneously displayable by the upgraded Independent Sub pixel Drive technology.


(Patent No.8,259,034B2)



*Customized viewer is required to display images with enhanced resolution by the Independent Sub pixel Drive technology
*Independent Sub pixel Drive technology is built in MS series only


Remote grayscale check and remote calibration functions

DICOM GSDF Conformance testing and calibration can be remotely accomplished. These features minimize the burden on display administrators.




Special AR coating for film-like black and improved sharpness

Special AR coating technology addresses properties of focus, noise reduction, contrast, and viewing angle achieving film-like black and accurate reproduction of images.



The special AR coating reduces diffuse reflection and improves properties of noise, focus, contrast and viewing angle.




Provided beads diffusely reflect the light to reduce background appearance mirrored on the screen. However, transmitted light (Displayed image) is also diffusely reflected causing focus loss and increased noise.

*The images explain general ideas of each mechanism and may be different from the actual structures.

Uniformity equalizer


Is built in to achieve highly accurate luminance and color uniformity across the screen.



* Color uniformity equalizer is built in color models only.
* Images shown are for illustrative purposes only.

10-bit grayscale with DisplayPort connections

With the monochrome models, 1021 or 10-bit shades of grayscale are simultaneously displayed from a palette of 12,277 grayscale steps. This capability provides doctors with finer and crisper images for them to be more confident in their readings.



* 10-bit capable viewing software is required.

Next Generation Interface - DisplayPort

In addition to a DVI port, each i2 series display includes a new digital display interface, "DisplayPort". When using the DisplayPort, up to 1021 or 10-bit shades of gray are simultaneously displayed. This enables smooth and accurate display of subtle differences in shades of gray. Additionally, 1064.33 million colors (10-bit in each R, G, B) are simultaneously displayed on our color model.



*10-bit viewer is required to display 10-bit images

User-friendly Functions

User-selectable display configurations

Luminance/gamma settings are selectable from three preset levels according to the needs. User-selectable configurations enable stress free operations without specialized settings.



OSD information display

At your fingertips, you can view current display status and information, including actual measurement of luminance, calibration settings, total operating hours as well as model name and serial number.



LED indicator

A glance at the LED indicator tells you the display's current operating status.




Display Quality Control

Medivisor® Series

(Optional software)

The Medivisor Series is a series of software to collectively support display quality control from acceptance and periodic constancy testing to constant monitoring, to calibration.



Ecological Technology – Considering the Global Environment



We are committed to providing high performance display systems that are ecological and environmentally friendly. We strive to create green IT initiatives and be a part of building a clean energy future. In effort to achieve this, we have incorporated new power-saving features in our i2 series displays. Our advanced power saving function dims the backlight as the screensaver activates, thereby reducing power consumption and preventing unnecessary backlight deterioration, resulting in a longer lasting display. Our internal power supply system includes a newly improved power save mode, which allows the display to enter standby mode with less than 2 watts of energy consumption.

*Optional software Calibration Kit is required to set up the Advanced Power Savings feature.

Color



3 Megapixel 21.3" Color Display

CCL358i2

CCL358i2/AR (Special AR Coating)
CCL358i2/F (Protective Filter)

21.3"

DisplayPort & DVI-D

800

cd/m²

1400:1

Calibration function

16Bit LUT

LED Backlight

10-bit display

OSD

Luminance Uniformity Correction

Hardware Pivot

LED Indicator



2 Megapixel 21.3" Color Display

CCL258i2

CCL258i2/AR (Special AR Coating)
CCL258i2/F (Protective Filter)

21.3"

DisplayPort & DVI-D

900

cd/m²

1400:1

Calibration function

16Bit LUT

LED Backlight

10-bit display

OSD

Luminance Uniformity Correction

Hardware Pivot

LED Indicator

Worldwide Medical Safety and EMI Standards

TOTOKU medical image displays comply with various stringent worldwide medical standards. They ensure safety and reliability required for use in medical facilities.

